



PRODUCT DATA

MEGADUR ACRYLIC PRIMER

Acrylic

DESCRIPTION

Clear, water resistant acrylic primer solvent diluted.

RECOMMENDED USE

MEGADUR has great penetration and adheres excellent on surfaces which will be painted with emulsion paints, exterior wall paints and sealant. It is suitable primer for porous substrates like plaster, cement, bricks, old coats, water paints and lime. It insulates dirty surfaces from smokes and mildew.

PHYSICAL DATA

- **Shade:** Transparent
 - **Theoretical spreading rate:** 13 –15 m²/Lt depending on substrate absorbency
 - **Drying time:**
 - **Dry to touch:** 1 hour 20° C 50 % Related humidity
 - **Final:** 3 hours 20° C 50 % Related humidity
 - **Recoat time:** after 2 hours
-

SURFACE PREPARATION

All the surfaces must be clean and free from grease and dust.

APPLICATION DETAILS

- The product is applied by spray gun, roll and brush.
 - Dilution: Walls : 100 % with WHITE SPIRIT or solvent N° 402.
Roofs : till 30 % with WHITE SPIRIT or solvent N° 402.
 - Tools cleaning: with solvent N° 401 or N° 402.
-

SAFETY

Use the product to well ventilated place.
Wear suitable protective gloves, eyeglasses and face protection

The above information and our technical advice-whether verbal or in writing-are given in good faith and according to our tests. Our advice does not release you from the obligation to verify the information currently provided and to test our products as to their suitability for the intended processes and uses.

