



PRODUCT DATA

Pro Acrylform

DESCRIPTION

General use emulsion paint, acrylic dispersion, water based.

RECOMMENDED USE

Pro Acrylform is suitable for the painting of interior and exterior surfaces.

PHYSICAL DATA

- **Shade:** White
- **Finish:** Matt
- **Volume solids:** 39 %
- **Specific gravity:** 1,45 Kg / Lt
- **Indicated dry film thickness:** Dry film 35 – 40 µm
- **Theoretical spreading rate:** 9 –11 m²/Lt
- **Drying time:**
 - **Dry to touch:** 20 min 23° C 50 % Related humidity
 - **Final:** 24 hours 23° C 50 % Related humidity

SURFACE PREPARATION

All the surfaces must be clean, dry and free from dust, rotten elements, oil e.t.c. Prime with undercoat MEGADUR and then apply two coats Pro Acrylform.

a) NEW UNCOATED SURFACES

On clean and dry surfaces of plaster, cement e.t.c. we apply one coat primer MEGADUR and then two coats Pro Acrylform.

b) REPAIR OF COATED SURFACES

On surfaces already painted without having any defects, we apply Pro Acrylform directly without any preparation. On surfaces with problems, we fill, sand and prime with MEGADUR and then we apply two coats Pro Acrylform.

On surfaces already painted with old water paints, we also prime with MEGADUR and then we apply one or two coats

Pro Acrylform. On metal surfaces, we prime with anticorrosive undercoat.

APPLICATION DETAILS

- The product is applied by roll, brush and airless spray.
- Dilution: till 10 % with water.
- Tools cleaning: with water and lather.

The above information and our technical advice-whether verbal or in writing-are given in good faith and according to our tests. Our advice does not release you from the obligation to verify the information currently provided and to test our products as to their suitability for the intended processes and uses.

