



PRODUCT DATA

HAMMER FINISH

Alkyd

DESCRIPTION

Alkyd enamel which offers the forged metal look to a surface.

RECOMMENDED USE

It is used to paint metallic surfaces, machinery, appliances, electrical panels, fence railings e.t.c.

PHYSICAL DATA

- **Shade:** Shades of our color shade.
 - **Finish:** High gloss
 - **Volume solids:** 47 % \pm 1
 - **Specific gravity:** 1,1 – 1,2 Kg / Lt
 - **Indicated dry film thickness:** Dry film 40 – 60 μ m
 - **Theoretical spreading rate:** 8 – 12 m² /Lt
 - **Drying time:**
 - **Dry to touch:** 8-10 min 23° C 50 % Related humidity
 - **Final:** 2 - 4 hours 23° C 50 % Related humidity
-

SURFACE PREPARATION

All the surfaces must be dry and clean before application of the paint. We can use it without primer.

APPLICATION DETAILS

- **Stir the paint slowly and carefully without mechanical means.** The product is applied by spray gun, airless and by brush on smaller surfaces.
 - Dilution: 0 – 3 % with solvent N° 401.
 - Tools cleaning: with solvent N° 401.
-

SAFETY

Use the product to well ventilated place.
Wear suitable protective gloves, eyeglasses and face protection.

The above information and our technical advice-whether verbal or in writing-are given in good faith and according to our tests. Our advice does not release you from the obligation to verify the information currently provided and to test our products as to their suitability for the intended processes and uses.