



PRODUCT DATA

ZAGPE

Alkyd

DESCRIPTION

Fast drying paint based on synthetic resins.

RECOMMENDED USE

It offers a coarse uniform surface of enough thickness to cover any imperfections.
For all uses of machinery, appliances e.t.c.

PHYSICAL DATA

- **Shade:** White, beige, green.
 - **Finish:** Satin
 - **Volume solids:** 48 % \pm 1
 - **Specific gravity:** 1,2 Kg / Lt
 - **Indicated dry film thickness:** Dry film 60 – 80 μ m
 - **Theoretical spreading rate:** 6 – 8 m² /Lt
 - **Drying time:**
 - **Dry to touch:** 15 min 23° C 50 % Related humidity
 - **Final:** 90 min 23° C 50 % Related humidity
-

SURFACE PREPARATION

In clean surfaces free from oils, dust, grease and rotten elements and in metallic surfaces protected with antirust primer, we apply one coat with high thickness without dilution or with slight dilution.

APPLICATION DETAILS

- Stir the paint well without mechanical means. The product is applied by airless or spray gun with large nozzle.
 - Dilution: 0 – 3 % with solvent N° 401.
 - Tools cleaning: with solvent N° 401.
-

SAFETY

Use the product to well ventilated place.
Wear suitable protective gloves, eyeglasses and face protection.

The above information and our technical advice-whether verbal or in writing-are given in good faith and according to our tests. Our advice does not release you from the obligation to verify the information currently provided and to test our products as to their suitability for the intended processes and uses.