



## PRODUCT DATA

# ACRYLFORM WALL PAINT SOLVENT DILUTED

Acrylic

### *DESCRIPTION*

ACRYLFORM is acrylic wall paint solvent diluted with excellent adhesion on surfaces. It has fast drying, it is weather resistant and resistant to atmospheric pollution.

### *RECOMMENDED USE*

ACRYLFORM is suitable for the painting of surfaces of cement faces, plaster, bricks and tiles.

### *PHYSICAL DATA*

- **Shade:** Various shades
- **Theoretical spreading rate:** 10 –12 m<sup>2</sup>/Lt
- **Drying time:**
  - **Dry to touch:** 2 hours 23° C 50 % Related humidity
  - **Recoat time:** after 8 hours

### *SURFACE PREPARATION*

On surfaces prepared with primer MEGADUR, we apply one or two coats.

### *APPLICATION DETAILS*

- The product is applied by spray gun, roll and brush.
- Dilution: 10 - 20 % with solvent N° 401 or N° 402.
- Tools cleaning: with solvent N° 401 or N° 402.

### *SAFETY*

Use the product to well ventilated place.  
Wear suitable protective gloves, eyeglasses and face protection

The above information and our technical advice-whether verbal or in writing-are given in good faith and according to our tests. Our advice does not release you from the obligation to verify the information currently provided and to test our products as to their suitability for the intended processes and uses.

