



## PRODUCT DATA

# MONOTIKO

### DESCRIPTION

Acrylic water based sealant with great water impenetrability.

### RECOMMENDED USE

MONOTIKO has great adherence and elasticity and is most suitable for insulating roofs and northern facing walls from moisture. It's exceptional elasticity allows it to follow any surface fluctuations, or even the capillary cracks on the wall.

### PHYSICAL DATA

- **Shade:** White
- **Finish:** Satin
- **Volume solids:** 53 %
- **Specific gravity:** 1,2 Kg / Lt
- **Indicated dry film thickness:**
  - Dry film 250 – 500 µm for roofs
  - Dry film 80 – 100 µm for northern walls
- **Theoretical spreading rate:** 1 – 2 m<sup>2</sup>/Lt for roofs  
5 – 7 m<sup>2</sup>/Lt for northern walls
- **Drying time:**
  - **Dry to touch:** 30 min 23° C 50 % Related humidity
  - **Final:** 24 hours 23° C 50 % Related humidity

### SURFACE PREPARATION

All the surfaces must be clean, dry and free from dust, rotten elements, oil e.t.c. Prime two coats with undercoat MEGADUR for roofs and one coat MEGADUR for walls and then apply two coats MONOTIKO.

### APPLICATION DETAILS

- The product is applied by roll, brush and airless spray.
- Dilution: for roofs, dilute the first coat 30-40 % with water. Follow the cross painting for the second coat without dilution.
- Tools cleaning: with water and lather.

The above information and our technical advice-whether verbal or in writing-are given in good faith and according to our tests. Our advice does not release you from the obligation to verify the information currently provided and to test our products as to their suitability for the intended processes and uses.

