



PRODUCT DATA

ACRYL 2K

Polyurethane

DESCRIPTION

ACRYL 2K is a polyurethane based paint of two components.

RECOMMENDED USE

It is used for the painting of cars, yachts, machines and metallic surfaces. It is UV stable and generally to the weather conditions.

PHYSICAL DATA

- **Shade:** Various RAL shades
 - **Finish:** High gloss
 - **Volume solids:** 50 %
 - **Specific gravity:** 1 – 1,2 Kg / Lt
 - **Indicated dry film thickness:** Dry film 30 – 40 µm
 - **Theoretical spreading rate:** 10 –12 m²/Lt
 - **Drying time:**
 - **Dry to touch:** 30 – 40 min 23° C 50 % Related humidity
 - **Final:** 5 – 6 hours 23° C 50 % Related humidity
-

SURFACE PREPARATION

All the surfaces must be free from grease, rust and dust. We apply one or two coats in a surface prepared by anticorrosive primer.

APPLICATION DETAILS

- Stir the paint well before its use. The product is applied by spray gun, airless and by brush on smaller surfaces.
 - Ratio A' COMPONENT/ B' COMPONENT:
2A / 1B p.b.V
 - Pot life : 6 – 8 hours
 - Dilution: after the mix of the two components, 10 % dilution with solvent N° 301.
 - Tools cleaning: with solvent N°301 or N° 201 or N° 601.
-

SAFETY

Use the product to well ventilated place.
Wear suitable protective gloves, eyeglasses and face protection.

The above information and our technical advice-whether verbal or in writing-are given in good faith and according to our tests. Our advice does not release you from the obligation to verify the information currently provided and to test our products as to their suitability for the intended processes and uses.